



# KUBE

up to 26 gal/day (100 l/day)

STANDARD DECONTAMINATION SYSTEMS WITH OPTIONS



Capacity: **Up to 26 gallons per day** (100 l/day)  
 Effluent: **Water-like**  
 Storage capacity: **6.6 gallons** (25 liters)



Utilities: **Electricity**  
**Single-phase 110 V - 60 Hz - 1.1 kW - 5 A**



Treatment program: 275°F (135°C) for 2 minutes (adjustable)  
 Decontamination: F<sub>0</sub> 50



Fully automatic operation with monitored cycles  
 Remote control available  
 Batch report



No use of chemicals  
 Safe for the workers and for the environment



Layout: **24" x 28"** (600 x 700 mm) - **connections included**

Height: **32"** (820 mm)

Model with **Containment option**:

Layout: **25" x 31'** (640 x 800 mm) - **connections included**

Height: **48"** (1,220 mm)

## Stop autoclaving liquids, using bleach or paying for off-site treatment!

- Guaranteed decontamination
- Validation of the treatment efficiency by sensors
- Automatic and monitored cycles

### Connection to:

- Biosafety cabinets to collect & treat effluent directly
- Emergency showers
- Beneath existing sinks

### KUBE MODEL

Patents: FR1355689 / EP14738747.6 / CA2915774

