



MICROSTEAM

up to 260 gal/day (1,000 l/day)

STANDARD DECONTAMINATION SYSTEMS WITH OPTIONS



Capacity: **Up to 260 gallons per day** (1,000 l/day)
Effluent: **Water-like**

Storage capacity: **185 gallons** (700 liters)
Option: **260 gallons** (1,000 liters)



Utilities: **Steam**
Single-phase 110 V - 60 Hz - 1 kW - 9.5 A
(excluding steam generator)
Steam: 65 psig 4.5 barg - 24 kW - 30 kg/h
With energy recovery section
No chilled water required



Treatment program: 275°F (135°C) for 2 minutes (adjustable)
Decontamination: F₀ 50



Layout: **52" x 76"** (1,320 x 1,930 mm)
Height : **87"** (2,220 mm) - for a 185-gallon storage capacity
95" (2,420 mm) - for a 260-gallon storage capacity
Including vent filter

- Specifically designed for placement in very tight spaces, this system is very easy to install in existing rooms
- Tested in our workshops before shipment, it will be fully operational as soon as plugged
- If no steam available on site, a steam generator can be integrated with the skid as an option.

Automatic operation

- Fully automated, the PLC controls and monitors all the cycles for a safe operation

MICROSTEAM MODEL

